



BIV/V - Ch. E21...69 Log-Periodic TX20L, Antenna / Aerial

Article number: 108185

Product description:

Log-Periodic TX20L

- Suitable for poor reception conditions, with reflections (shadows) but where signal level is OK
- Rear mounted F-connector. Flat wideband response.
- Good impulse noise rejection for stable digital reception. Rugged construction.

Specifications

ORDER INFORMATION	
EAN Number	5702661081859
CHARACTERISTICS	
Type	Log Periodic 20 element
FREQUENCY	
Band (frequency)	BIV/V
Channels	21...69
Frequency range UHF	470...862 MHz
GAIN	
Gain	4...9 dBi
Gain @ 474 MHz (Ch. 21)	5 Typ dBi
Gain @ 602 MHz (Ch. 45)	8 Typ dBi
Gain @ 786 MHz (Ch. 60)	4.8 Typ dBi
LOSS	
Rejection @ 862 MHz (LTE U6)	5.5 Typ dB
ELECTRICAL	
Front to back ratio - horizontal	>12 dB
Impedance	75 Ω
CONNECTORS	
Connector Type	F-female
MECHANICAL	
Elements	20
Packaging Depth	0,395 m
Packaging Height	0,050 m

Total Weight	0,440 kg
Packaging Width	0,295 m
Main Material	Aluminium
Net Weight	0,340 kg
Remarks	VSWR: <4.2
Tara Weight	0,100 kg
Packaging Volume	0,006 m3
